



GeneNetwork: an interactive tool for reconstruction of genetic networks using microarray data

Chia-Chin Wu¹, Hsuan-Cheng Huang^{1,2,*}, Hsueh-Fen Juan^{3,4} and Shui-Tein Chen^{1,3,5,*}

¹Institute of Biological Chemistry and Genomics Research Center, Academia Sinica, Taipei, Taiwan, ²Institute of Bioinformatics, National Yang-Ming University, Taipei, Taiwan, ³Department of Life Science, Institute of Molecular and Cellular Biology, Institute of Biochemical Sciences, National Taiwan University, Taipei, Taiwan, ⁴Department of Chemical Engineering, National Taipei University of Technology, Taipei, Taiwan and ⁵ALPS Biotech Co., Ltd, Taipei, Taiwan

Received on November 12, 2003; revised on April 29, 2004; accepted on July 5, 2004
Advance Access publication July 22, 2004

ABSTRACT

Summary: Inferring genetic network architecture from time series data generated from high-throughput experimental technologies, such as cDNA microarray, can help us to understand the system behavior of living organisms. We have developed an interactive tool, GeneNetwork, which provides four reverse engineering models and three data interpolation approaches to infer relationships between genes. GeneNetwork enables a user to readily reconstruct genetic networks based on microarray data without having intimate knowledge of the mathematical models. A simple graphical user interface enables rapid, intuitive mapping and analysis of the reconstructed network allowing biologists to explore gene relationships at the system level.

Availability: Download from <http://genenetwork.sbl.bc.sinica.edu.tw/>

Contact: hchuang@gate.sinica.edu.tw; bcchen@gate.sinica.edu.tw

Supplementary information: Supplement documentation of algorithms for the four approaches is downloadable at the above location.

INTRODUCTION

Most biochemical relationships among genes, proteins and other organic substrates are known to be many-to-many, meaning that one component can have many functions and one function can be influenced by many components. To understand these complex relationships, the structure of a biological system, such as regulatory relationships of genes, needs to be identified first. Reverse engineering methods provide a good way to model genetic interactions as network

diagrams of interacting elements based on time-course gene-expression data generated from cDNA microarray experiments. The reconstructed genetic network can then be validated experimentally.

Because most genetic network models are mathematically and computationally complicated, a full understanding of the logic and complex behavior of genetic networks will require the development of tools for the computational and visual exploration of complex networks. Although several previous attempts have been made to visualize pathways from prior known knowledge and to simulate system dynamic processes in software packages (Breitkreutz *et al.*, 2003; Dahlquist *et al.*, 2002; Shannon *et al.*, 2003), none of them allow users to infer genetic networks from experimental gene-expression data using reverse engineering approaches. This paper presents a computational and user-friendly software tool, GeneNetwork, to visually reconstruct genetic networks from gene-expression data using reverse engineering models. It can be used by biologists with only a minimal amount of mathematical training, yet gives them the power to explore a wide range of sophisticated questions about genetic networks.

OVERVIEW OF THE SOFTWARE

The architecture of GeneNetwork, written in C++, is outlined in Figure 1. The work flow for GeneNetwork is as follows: (1) input experimental data in tab-delimited text format; (2) interpolate data through the Interpolation Controller if the number or sets of experimental data points are insufficient to initiate the inference calculations; (3) implement reverse engineering inference approaches through the Modeling Controller to generate the gene regulation matrix that describes

*To whom correspondence should be addressed.




Fig. 1. The architecture of GeneNetwork.

how genes regulate each other; (4) automatically draw the network for visualization, based on the regulation matrix; (5) compare the inferred intuitive network with on-line databases such as KEGG (Kanehisa *et al.*, 2004), based on the information from the Network Graph Viewer and the Information Viewer; and (6) review the proposed sets of experiments and generate hypothesis. These high-level capabilities of GeneNetwork are described as follows.

Interpolation Controller

The required minimum number of data time points depends on the number of variables in the mathematical model for genetic network inference. If the time points of experimental data are insufficient to fulfill the requirement of the specified model, the network analysis can be initiated by interpolation of the time series data points. The Interpolation Controller provides three selections of data interpolation approaches: linear, Lagrange polynomial and cubic spline interpolation (Constantinides and Mostoufi, 1999).

Modeling Controller

Various reverse engineering algorithms have been used to model genetic regulatory networks (de Jong, 2002). GeneNetwork offers four different inference models to extract the 'gene regulation matrix' from the gene expression data: (1) the linear model (D'haeseleer *et al.*, 1999) is a continuous method that uses linear ordinary differential equations to

describe the system; (2) the S-system (Kikuchi *et al.*, 2003) is an approximation of traditional rate laws with a uniform type of non-linear ordinary differential equation in which the component processes are characterized by the power-law functions; (3) the Boolean network (Liang *et al.*, 1998) is a logical description in which variables and functions (the relationships between the components) are simply presented as ON or OFF; and (4) the dynamic Bayesian network (de Jong, 2002) stochastically models causality between genes over time series data. For the latter three models, the genetic algorithm is applied to effectively search for the optimal point in the large solution space and to learn network structure (Repsilber *et al.*, 2002). Users can change the parameters in the four approaches through the Modeling Controller.

Network Graph Viewer/Information Viewer

To extract valuable information from the gene regulation matrix, GeneNetwork embraces several network visualization layouts. A network diagram is presented with nodes corresponding to genes and edges indicating relations between the genetic network components. Information on the network structure and genes, from the gene regulation matrix and input information, can be shown on the Information Viewer. Clicking on any node reveals the biological processes that involve the selected gene and its relation to others. GeneNetwork is fully customizable and allows users to define personal settings to generate interaction networks by manipulating

several graphical setting options, such as linkage changes, gene selections, gene searches, font and graph settings, etc.

DISCUSSION

The four inference models in GeneNetwork have different advantages and weaknesses and users can select the appropriate model based on their requirements. The linear model is a gross simplification for most biological systems but it offers an easy method to infer genetic network; the assumptions may be unrealistic. The S-system can capture the non-linear system dynamics, although the method exerts large computational cost to search for the optimal solution. In Boolean network model, the regulatory control of gene expression is expressed by logical rules, which allows large-scale genetic networks to be analyzed in an efficient way. The advantages of the dynamic Bayesian network include the ability to model stochasticity, to incorporate prior knowledge, and to handle hidden variables and missing data in a principled way. Nevertheless, determining the optimal network structure of Bayesian networks is an NP-hard problem. Furthermore, discretization of gene expression in both Boolean and Bayesian models would induce information loss.

In the Supplementary material, we provide detailed descriptions of the four methods and an application of the *Saccharomyces cerevisiae* cell-cycle gene-expression data (Spellman *et al.*, 1998) to GeneNetwork. Many of the inferred gene relations are known to be involved in the *S.cerevisiae* cell-cycle pathway.

FUTURE WORKS

The future works will focus on the automatic integration with on-line databases to provide more up-to-date genome information to a user while using GeneNetwork. In addition, the visualization capabilities for large-scale network layout will be enhanced.

ACKNOWLEDGEMENT

We thank John Y. Lin for revising the manuscript. We gratefully acknowledge the support of the National Research

Program for Genomic Medicine of National Science Council, Taiwan (NSC 91-3112-13-001-002 and NSC 92-3112-B-027-001).

REFERENCES

- Breitkreutz, B.J., Stark, C. and Tyers, M. (2003) Osprey: a network visualization system. *Genome Biol.*, **4**, R22.
- Constantinides, A. and Mostoufi, N. (1999) *Numerical Methods for Chemical Engineers with Matlab Applications*. Prentice-Hall Inc., NJ.
- Dahlquist, K.D., Salomonis, N., Vranizan, K., Lawlor, S.C. and Conklin, B.R. (2002) GenMAPP: a new tool for viewing and analyzing microarray data on biological pathways. *Nat. Genet.*, **31**, 19–20.
- D'haeseleer, P., Wen, X., Fuhrman, S. and Somogyi, R. (1999) Linear modeling of mRNA expression levels during CNS development and injury. *Pac. Symp. Biocomput.*, **4**, 41–52.
- de Jong, H. (2002) Modeling and simulation of genetic regulatory systems: a literature review. *J. Comput. Biol.*, **9**, 67–103.
- Kanehisa, M., Goto, S., Kawashima, S., Okuno, Y. and Hattori, M. (2004) The KEGG resource for deciphering the genome. *Nucleic Acids Res.*, **32**, 277–280.
- Kikuchi, S., Tominaga, D., Masanori, A. and Tomita, M. (2003) Dynamic modeling of genetic networks using genetic algorithm and S-system. *Bioinformatics*, **19**, 643–650.
- Liang, S., Fuhrman, S. and Somogyi, R. (1998) REVEAL: a general reverse engineering algorithm for inference of genetic network architectures. *Pac. Symp. Biocomput.*, **3**, 18–29.
- Repsilber, D., Liljenstrom, H. and Andersson, S.G. (2002) Reverse engineering of regulatory networks: simulation studies on a genetic algorithm approach for ranking hypotheses. *Biosystems*, **66**, 31–41.
- Shannon, P., Markiel, A., Ozier, O., Baliga, N.S., Wang, J.T., Ramage, D., Amin, N., Schwikowski, B. and Ideker, T. (2003) Cytoscape: a software environment for integrated models of biomolecular interaction networks. *Genome Res.*, **13**, 2498–2504.
- Spellman, P.T., Sherlock, G., Zhang, M.Q., Iyer, V.R., Anders, K., Eisen, M.B., Brown, P.O., Botstein, D. and Futcher, B. (1998) Comprehensive identification of cell cycle regulated genes of the yeast *Saccharomyces cerevisiae* by microarray hybridization. *Mol. Biol. Cell*, **9**, 3273.